



Yellow Pin Bow Shackles - Economy Range

with screw collar pin

Material: Bow and pin high tensile steel, Grade 6
Standard: Generally to US Fed Spec RR-C-271
Finish: Hot dipped galvanised
Certificate: As standard an EC declaration of conformity is supplied, also upon request a certificate of basic raw material

working load limit	diameter bow	diameter pin	diameter eye	inside width	inside length	width bow	product code	weight each
tons	a mm	b mm	c mm	d mm	e mm	f mm		kg
0.33	5	6	14	9.5	22	15	11001C	0.03
0.50	6	8	16	12	29	20	11002C	0.05
0.75	8	10	19	13.5	31	21	11003C	0.09
1.00	10	11	23	17	37	26	11004C	0.14
1.50	11	13	27	19	43	29	11005C	0.17
2.00	13	16	30	20	48	33	11006C	0.33
3.25	16	19	38	27	60	43	11007C	0.62
4.75	19	22	46	32	71	50	11008C	1.07
6.50	22	25	53	36	84	58	11009C	1.64
8.50	25	28	61	43	95	68	11010C	2.28
9.50	28	32	68	46	108	74	11011C	3.36
12.00	32	35	76	51	119	82	11012C	4.31
13.50	35	38	84	57	133	92	11013C	6.14
17.00	38	42	92	60	146	98	11014C	7.81
25.00	45	50	106	73	177	127	11015C	12.61
35.00	50	57	119	83	197	138	11016C	18.33
55.00	65	70	145	105	260	185	11018C	37.90

