

Yellow Pin Dee Shackles - Economy Range

with screw collar pin

Material:
Standard:
Finish:
Certificate:

Bow and pin high tensile steel, Grade 6
Generally to US Fed Spec RR-C-271
Hot dipped galvanised
As standard an EC declaration of conformity is supplied,
also upon request a certificate of basic raw material

working load limit	diameter bow	diameter pin	diameter eye	inside width	inside length	product code	weight each
tons	a mm	b mm	c mm	d mm	e mm		kg
0.50	6	8	16	12	22	11502C	0.05
0.75	8	10	19	13.5	26	11503C	0.08
1.00	10	11	23	17	32	11504C	0.13
1.50	11	13	27	19	37	11505C	0.20
2.00	13	16	30	20	41	11506C	0.27
3.25	16	19	38	27	51	11507C	0.57
4.75	19	22	46	32	60	11508C	1.19
6.50	22	25	53	36	71	11509C	1.43
8.50	25	28	61	43	81	11510C	2.16
9.50	28	32	68	46	90	11511C	3.06
12.00	32	35	76	51	100	11512C	4.11
13.50	35	38	84	57	111	11513C	5.28
17.00	38	42	92	60	122	11514C	7.24
25.00	45	50	106	73	146	11515C	12.14
35.00	50	57	119	83	171	11516C	16.86
55.00	65	70	145	105	203	11518C	32.65

