

Green Pin® Standard Dee Shackles G-4151

with screw collar pin

Material: Body and pin high tensile steel, Grade 6, quenched and tempered
Safety Factor: MBL equals 6 x WLL
Standard: EN 13889 and meets performance requirements of US Fed Spec RR-C-271, Type IVB Class 2, Grade A
Finish: Hot dipped galvanised
Temp Range: Minus 20°C up to 200°C
Certificate: As standard an EC declaration of conformity is supplied, also upon request a basic raw material cert, manufacturer test cert, inspection cert and DNV cert (2t above)

working load limit	bow dia	pin dia	eye dia	width eye	width inside	length inside	length	length bolt	product code	weight each
tons	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm		kg
0.33	5	6	12	5	9.5	19	33	29.5	11501A	0.02
0.5	7	8	16.5	7	12	22	41.5	38	11502A	0.05
0.75	9	10	20	9	13.5	26	50	46.5	11503A	0.09
1	10	11	22.5	10	17	32	59	54	11504A	0.14
1.5	11	13	26.5	11	19	37	68	59.5	11505A	0.19
2	13.5	16	34	13	22	43	81	73	11506A	0.32
3.25	16	19	40	16	27	51	97	89	11507A	0.54
4.75	19	22	46	19	31	59	112	103	11508A	0.87
6.5	22	25	52	22	36	73	134	119	11509A	1.34
8.5	25	28	59	25	43	85	154	137	11510A	2.08
9.5	28	32	66	28	47	90	167	153	11511A	2.77
12	32	35	72	32	51	94	180	170	11512A	3.72
13.5	35	38	80	35	57	115	209	186	11513A	5.14
17	38	42	88	38	60	127	230	203	11514A	6.85
25	45	50	103	45	74	149	271	243	11515A	11.45
35	50	57	111	50	83	171	305	272	11516A	16.86
42.5	57	65	130	57	95	190	345	310	11517A	24.61
55	65	70	145	65	105	203	376	344	11518A	32.65

